



IDSmart Self-Return Kiosk

This Self-return Station offers simple and quick **24/7** book return service to patrons. When integrated with the Integrated Library System (ILS) back-end for data synchronization and update, this equipment features location flexibility, easy installation, and instant setup, and could serve as a best choice in introducing self-assisted services for the library.

Features

- Offers patrons 24/7 easy and quick book return self-service, breaking the limit in time and location of library service.
- Compact and streamlined design with high flexibility in physical placement; the best choice for libraries with limited space.
- Complete and thorough system design with short installation and setup time, requiring no infrastructure overhead.
- Super simple and easy user operation, resulting in instant book return.
- High mobility, supporting temporary need of location replacement or movement.
- Features areas of VI for exclusive visual presentation.
- Communicates with the ILS for real-time data synchronization.
Able to inform librarian proactively in book-full condition.
- Easy management and maintenance; able to connect with remote monitoring mechanism for instant equipment control at finger tips.



Specification

IDSmart Self-return Station : Specification

Equipment size	<ul style="list-style-type: none"> (W)750mm*(D) 818mm*(H)1300mm
Book return gate	<ul style="list-style-type: none"> Automatic door with safety shutter and pressure sensor Doubled operation safety
Book return sensing	<ul style="list-style-type: none"> RFID : HF or UHF *RFID + Barcode: total sensor technology coverage
Operating panel	<ul style="list-style-type: none"> 15" capacitive touch screen
Receipt printer	<ul style="list-style-type: none"> Thermal receipt printer Receipt width 80mm
Built-in industrial PC Administration	<ul style="list-style-type: none"> Dual-core CPU or above Memory 2GB or more Storage space 250GB or more Operating system Windows 7 or above
Accessories	<ul style="list-style-type: none"> Keyboard Mouse
Operating mode	<ul style="list-style-type: none"> Automatic Manual
Networking protocol	<ul style="list-style-type: none"> TCP/IP
Power specification	<ul style="list-style-type: none"> 110 ~ 240V
Optional components	<ul style="list-style-type: none"> Barcode reading device UPS Remote device monitoring mechanism Customized VI design



*Need to match the purchase item

IDSmart Self-Return Kiosk

MITAC  **MITAC INFORMATION TECHNOLOGY CORP.**

Email:marketing@mitac.com.tw

Head Office

ADD:10F, No. 187, Sec. 2, Tiding Blvd., Neihu Dist., Taipei City 114, Taiwan, R.O.C.

TEL: +886-2-2657-6666 FAX: +886-2-2657-6046