





This Self-service Locker can easily extend the serviceability of the library by providing convenient and independent book delivery to the patrons. Integrated with the library management mechanism, it creates a new, innovative, and easy-to-set-up service option which features 24/7 availability and more self-assist and freedom for the patrons to enjoy library services.

features

- 1. The best helper for the patrons to fetch reserved books by themselves.
- 2. Easy to set up and extend library service boundary effectively.
- 3. Enables 24/7 uninterrupted services which is more convenient to patrons.
- 4. Simple and fast to operate, requiring only 3 steps to complete the fetching/borrowing of books.
- 5. Easy to manage and maintain; Can be configured with remote monitoring mechanism for controlling all devices at finger tips.
- 6. Compact and lightweight; Flexible in location planning and placement.
- 7. Modular design with number of cabinets and configuration customizable; the configuration can also be expanded at any time.
- 8. isual Identity for the equipment can be customized to create an exclusive appearance.

Specification

10.0	
IDSmart Self-service Locker: Specification	
Standard model	 A total of 40 independent cabinet in 2 vertical cabinet groups
	• Size: (W)1970mm*(D)500mm*(H)1800mm
Space of a cabinet	 No less than (W)240mm*(D)290mm*(H)80mm
Operating panel	19" capacitive touch screen
Receipt printer	Thermal receipt printer
	Receipt width 80mm
Two-in-one reader slot	HF Card Reader
	Barcode Reader
Built-in industrial PC	Dual-core CPU or above
	Memory 2GB or more
	Storage 320GB or more
	 Operating system Windows 7 or above
Librarian operating area	Keyboard
	Mouse
	Handheld barcode reader
	Built-in shelf
Audio feature	Built-in speaker
Guiding lights	Red and green LED lights
Operating mode	Automatic
	Manual
Networking protocol	• TCP/IP
Power specification	• 110 ~ 240V
(Optional) Expandable	20 cabinet units per cabinet group
vertical cabinet group	Left size:(W)660mm*(D)500mm*(H)1800mm
	Middle size:(W)660mm*(D)500mm*(H)1800mm
	• Right size:(W)660mm*(D)500mm*(H)1800mm
(Option) Other components	Surveillance system and digital surveillance camera
	• UPS
	Remote device monitoring mechanism
	Customized VI design





MITAC MITAC INFORMATION TECHNOLOGY CORP.

Email:marketing@mitac.com.tw

ADD:10F, No. 187, Sec. 2, Tiding Blvd., Neihu Dist., Taipei City 114, Taiwan, R.O.C. TEL: +886-2-2657-6666 FAX: +886-2-2657-6046